



Models FTM/FTMR Swivel Mount Cylinders

Models FSM/FSMR Nose Mount Cylinders

FOR MODELS FTM & FSM DOUBLE ACTING: A + STROKE
 FOR MODELS FTMR & FSMR SPRING RETURN: A + (STROKE X 2)
 FOR MODELS FTMR & FSMR UP TO 1/2" STROKE SPRING RETURN: A + (STROKE + 1")

DIMENSIONAL DATA

| Bore Size | A | B | C | D | E | H | J | K | L | M | R | S | T |
|-------------------------------|--------------------------------|--------------------------------|--------------------------------|------|------|--------|-----|------|-----|---------|------|-------------------------------|-----|
| 1/2 | 1 ¹ / ₁₆ | 1 ¹ / ₄ | 1 ³ / ₁₆ | 1/2 | 9/16 | 1/2-20 | 1/4 | 1/4 | 1/2 | 1/4-28 | 9/16 | 3/4 | 3/4 |
| 3/4 | 1 ¹ / ₁₆ | 1 ¹ / ₄ | 1 ³ / ₁₆ | 1/2 | 9/16 | 5/8-18 | 1/4 | 1/4 | 1/2 | 1/4-28 | 9/16 | 1 | 3/4 |
| 1 ¹ / ₈ | 1 ¹ / ₁₆ | 1 ⁵ / ₁₆ | 1 ⁵ / ₁₆ | 9/16 | 5/8 | 5/8-18 | 3/8 | 5/16 | 1/2 | 5/16-24 | 5/8 | 1 ³ / ₈ | 3/4 |

Porting for all sizes is 1/8" N.P.T.F.

NOTE: For Models Digit-Air with bumpers, contact factory for stock stroke sizes and add 1/2" to Dimension "A" for each bumper.

See Application Information for sensors and magnetic switch options, mounting accessories, special options, and ordering information.